

High Pressure Cleaner - heated with oil

Weidner Waschbär S550

The smallest hot water cleaner, is designed and built for "semi-professional application" for private use, in agriculture and trade. The applications of the S 550 are situations, where the use of hot water is necessary, i.e. grease and oil contamination and where space is limited or when working with a small budget only. The cleaning requirements should, however, not be too difficult, due to the limited pressure and water quantity. The standard accessories are complete with high pressure hose, trigger and steel lance with multifunction nozzle, the unit is immediately ready for use.

Waschbär 1132 LXT
Waschbär 1162 LXT
Waschbär 1152 KXT



The advantages are obvious:

- Low initial costs
- compact dimensions
- low weight
- easy transport, even in a car or estate car, as well as simple operation make these appliances indispensable for many smaller and medium cleaning tasks

A few outstanding advantages for this performance class::

- Cold or hot water operation possible
- Adjustable pressure and water volume
- Display of the present working pressure
- Chemicals injector
- Self-priming
- Highly effective with hot water operation
- Triplex pump with ceramic plungers

| model | order-no. | pressure max. | | volume max. l/h | Motor * | | temp. max.** | time delayed stop | dimensions W x H x D mm | weight kg | nozzle size | users-recommend. |
|-------------------|--------------|---------------|------|-----------------|------------|-------------|--------------|-------------------|-------------------------|-----------|-------------|------------------|
| | | bar | PSI | | 230 V | 400 V | | | | | | |
| WASCHBÄR 1132 LXT | HWY 1132 LXT | 130 | 1950 | 660 | 3 kW/14,5A | 3-400V/50Hz | 40-140°C | • | 750x700x700 | 100 | 045 | ◻ ◻ ◻ |
| WASCHBÄR 1162 LXT | HWY 1162 LXT | 160 | 2400 | 540 | 3 kW/14,5A | | 40-140°C | • | 750x700x700 | 100 | 035 | ◻ ◻ ◻ |
| WASCHBÄR 1152 KXT | HWY 1152 KXT | 150 | 2175 | 660 | | 3,5 kW/7,5A | 40-140°C | • | 750x700x700 | 100 | 055 | ◻ ◻ ◻ |

* machines with special voltage on request ** with reduced quantity of water ◻ with Vario-Press no injector function

Weidner Waschbär S 2000

The professional range of hot water high pressure cleaners. Built for heavy duty operation in industry, craft and agriculture. For all applications, where solid dirt needs to be removed with hot water.

Waschbär 122LXTT
 Waschbär 147 KXTT
 Waschbär 148 KWPT
 Waschbär 182 KXRT
 Waschbär 183 KWPT
 Waschbär 220 KXRT



The main features are:

- triplexpump with ceramic plungers
- infinitely variable pressure and water volume
- upright heating coil with high efficiency, save energy and does not pollute the environment
- independent burner motor saves energy during cold water operation
- easy to operate control panel
- industrial motor for continuous operation
- the turning sense of the motor is regardless
- stainless steel cover

Standard accessories:

- 6 m electric cord
- 10 m quality high pressure hose
- pistol with hand protection
- stainless steel lance with nozzle

| model Waschbär S 2000 | order-no. | pressure max. | | volume max. l/h | Motor * | | temp. max. | time delayed stop | dimensions W x H x D mm | weight kg | nozzle size | users-recommend. |
|--------------------------|--------------|---------------|------|--------------------|-------------|------------|---------------|-------------------|-------------------------------|--------------|-------------|------------------|
| | | bar | PSI | | 230 V | 400 V | | | | | | |
| WASCHBÄR 122 LXTT | HWY 122 LXTT | 120 | 1750 | 660 l/h | 3,0kW/14,5A | 30-140°C** | • | 1100x740x770 | 140 | 05 | ■ | |
| WASCHBÄR 147 KXTT | HWY 147 KXTT | 150 | 2200 | 780 l/h | 3,5kW/7,5A | 30-140°C** | • | 1100x740x770 | 142 | 055 | ■ | |
| WASCHBÄR 148 KWPT | HWY 148 KWPT | 150 | 2200 | 780 l/h | 3,5kW/7,5A | 30-140°C** | • | 1100x740x770 | 142 | 055 | ■ | |
| WASCHBÄR 182 KXRT | HWY 182 KXRT | 180 | 2600 | 1000 l/h | 4,8kW/8,8A | 30-140°C** | • | 1100x740x770 | 142 | 06 | ■ | |
| WASCHBÄR 183 KWPT | HWY 183 KWPT | 180 | 2600 | 1000 l/h | 4,8kW/8,8A | 30-140°C** | • | 1100x740x770 | 142 | 06 | ■ | |
| WASCHBÄR 220 KXRT | HWY 220 KXRT | 160 | 2320 | 1200 l/h | 6,1kW/9,5A | 30-140°C** | • | 1100x740x770 | 148 | 065 | ■ | |

* machines with special voltage on request ** with reduced quantity of water




Weidner Waschbär S 2000 X-Class

In this range of machines you can choose among various different models: Single phase or three phase connection, oil heated or electrically heated with different pressure and water volumes. This ensures to find the right machine for your cleaning needs.

Waschbär S 2000, universal application in agriculture, trade and industry, for removal of heavy contamination in all areas. Cleanliness and hygiene in perfection.

Waschbär 203 KWPXT



The main technical advantages:

- Interpump pump by X-Class model
- drive wheel with foam filling
- brushed stainless steel covers in new design
- strengthened steering wheel
- new hand grip with cover fastening
- hour meter
- 400 bar, hp-hose with stainless steel lance

Complete equipment with:

- 6 m cable with plug
- 10 m high pressure hose
- pistol with hand protection
- turnable stainless steel lance with nozzle

| model | order-no. | pressure max. | | volume max. | Motor * | | temp. | time delayed stop | dimensions L x B x H | weight | nozzle size | users-recommend. |
|--------------------|---------------|---------------|------|-------------|-------------|-------------|--------|-------------------|----------------------|--------|-------------|------------------|
| | | bar | PSI | | l/h | 230 V | | | | | | |
| WASCHBÄR 203 KWPXT | HWY 203 KWPXT | 200 | 2900 | 1000 l/h | 1-230V/50Hz | 3-400V/50Hz | max.** | • | 1080x740x830 | 150 | 055 | ■ |