

High Pressure Cleaner - unheated



Standard equipment:

- transportation without strain due to the trolley
- 10 m quality high pressure hose
- pistol with hand protection, lance and pressure adjusting nozzle
- chemical dosing via injector
- motor with thermal injector
- direct drive without pulley and belts
- slow running triplexpump with 3 ceramic plungers
- industrial motor with 100% running time
- infinitely variable volume and pressure
- holder for pistol and accessories
- drawing of water is possible
- use of hot water up to 60° C
- multi utilisation due to availability of various accessories

Special application areas are, for instance:

Cleaning of agricultural machinery, milking parlors, stables, vehicles and industrial machinery and the building trade. Removal of most difficult dirt on building fronts, monuments, industrial floors, ideal for renovating buildings and concrete and professional stone cleaning.


The benefit of using this product is clear. Effective short working times, enormous energy savings and long useful life due to the high industrial quality.

model	order-no.	pressure max.		volume max. l/h	Motor *		temp max.**	time delayed stop	dimensions W x H x D mm	weight kg	nozzle size	users- recommend.
		bar	PSI		230 V 1-230V/50Hz	400 V 3-400V/50Hz						
WASCHBOY-132 R	HKY 132 LXTR	130	2000	660	3,1kW/14 A	60°C			290x320x520	34	045	■ ■
WASCHBOY-162 R	HKY 162 LXTR	160	2350	540	3,1kW/14 A	60°C			290x320x520	34	035	■ ■
WASCHBOY-132 F	HKY 132 LXTF	130	2000	660	3,1kW/14 A	60°C			540x460x810	46	045	■ ■
WASCHBOY-162 F	HKY 162 LXTF	160	2350	540	3,1kW/14 A	60°C			540x460x810	46	035	■ ■
WASCHBOY-133 A	HKY 133 LWPA	130	2000	660	3,1kW/14 A	60°C	•		290x320x520	34	045	■ ■
WASCHBOY-212	HKY 212 KRK	210	3050	1000		6,2kW/10A	60°C		580x950x910	61	05	■ ■ ○
WASCHBOY-212 A	HKY 212 KRKA	210	3050	1000		6,2kW/10A	60°C	•	580x950x910	61	05	■ ■ ○
WASCHBOY-213	HKY 213 KWP	210	3050	1000		6,2kW/10A	60°C		580x950x910	61	05	■ ■ ○
WASCHBOY-213 A	HKY 213 KWPA	210	3050	1000		6,2kW/10A	60°C	•	580x950x910	61	05	■ ■ ○

Weidner Waschboy X-Class

Rather than follow the general trend to manufacture cheaper with lower quality which is disadvantageous to you, Weidner created the X-class, a high pressure cleaner series with outstanding quality performances.

This means that only components of top quality are used for the production, only the best will do. It is not just only a saying, that a "Cat" pump has 9 lives. The benefits for you are obvious, you get a machine for heavy duty industrial use with highest reliability and good pay back due to extreme long living period. The entire stainless steel lay out makes it a good seller for the food industry.

<p>Waschboy 132 CA Waschboy 182 CA</p> 	<p>standard equipment: Waschboy X-Class:</p> <ul style="list-style-type: none"> • "Cat" high pressure pump • slow running triplexpump with 3 ceramic plungers • pump head out of brass • industrial motor with 100% running time • pump and motor separated by flexible clutch • no heat transfer from motor to pump • flexible coupling dampens torsion moments • time delayed pressure free total stop • stainless steel lay out of cover and entire casing • non marking tyres filled with special foam • 10 m quality high pressure hose • pistol short, lance with hand protection, turnable under pressure • chemical dosing via injector • direct drive without pulley and belts • infinitely variable volume and pressure • holder for pistol and accessories • drawing of hot or cold water is possible • use of hot water up to 85° C • multi utilisation due to availability of various accessories
---	--

model	order-no.	pressure max.		volume max. l/h	Motor *	temp. max.**	time delayed stop	dimensions W x H x D mm	weight kg	nozzle size	users-recommend.
		bar	PSI		3-400V/50Hz						
WASCHBOY 132 CA	HKY 132 C 23 A	130	2000	1380	6,2 kW/10A	85°C	•	780x680x680	70	12	■ ○
WASCHBOY 182 CA	HKY 182 C 15 A	180	2650	1000	6,2 kW/10A	85°C	•	780x680x680	70	06	■ ○

Weidner Waschboy

Weidner Waschboy 152/202/242 B cold water, high pressure jetting units



Standard equipment:

- Honda engine GX 340 LX
- High pressure hose, 10 m
- Double lance with pressure adjustment
- "Interpump" - quality pump
- Infinitely variable pressure and volume
- The pump is able to draw water due to slow running pump
- Automatic low oil cut of
- Automatic rpm. reducer
- Chemical tank 15l with chemical injector
- Elastic tyres for easy transport
- Triplex pump with 3 ceramic plungers
- Multi utilisation due to availability of various accessories

For all cleaning applications where standard units are not powerful enough, i.e.

- for cleaning of building fronts without chemicals
- for paint removal in spray booths
- cleaning of subways, tunnels and bridges
- also for professional monument and stone cleaning
- for building and concrete renovation
- for water sand blasting of armour
- or for gentle and quick bark removal form trees and logs
- and much, much more heavy duty cleaning possibilities

Efficiency,

- large surface capacity
- autonomy
- the saving of water, energy and time
- as well as the solution of real cleaning problems are only a few advantages of this mobile pressure cleaners

model	order-no.	pressure max.		volume max. l/h	Motor *	temp. max.	time delayed stop	dimensions W x H x D mm	weight kg	nozzle size	users-recommend.
		bar	PSI								
WASCHBOY 152 B	HKY 152 BXT	250	2250	660	3,9kW/4-stroke fuel motor	50°C		30x430x430	34	055	
WASCHBOY 202 B	HKY 202 BXRA	200	2900	1080	8kW/4-stroke fuel motor	50°C	•	1150x720x880	100	065	
WASCHBOY 240 B	HKY 242 BXRA	240	3480	1000	8kW/4-stroke fuel motor	50°C	•	1150x720x880	100	055	
WASCHBOY 350 E*	HKY 350 ENP	350	5250	1260	15kW/400V/50Hz/28,5A	50°C		910x680x680	190	-	
WASCHBOY 400 E*	HKY 400 EIP	400	5800	1500	22kW/400V/50Hz/64A	50°C		1030x1020x740	340	-	